



Model No.: **TLd-15W** **TLd-25W**
TLd-36W



MAIN FEATURES:

- Perfectly suitable to replace 35, 50 & 70 Watt CDMT track rail fixtures respectively.
- Available in CRI 80+ or 90+.
- Dimming method: Triac.
- With 3-phase track adapter or single-phase track adapter.
- The Max. movement for lamphead is 350D horizontally and 90D vertically.
- Popular for accent lighting and flood lighting.

LIGHT	CREE COB LED
INPUT VOLTAGE	100-120V / 220-240V AC, AC, 50-60Hz
DRIVER	CE, SAA, UL approved
DIMMABLE	Triac
INSTALLATION	On 4-pin or 3-pin track
HOUSING COLOR	Black, white, silver
OPERATING TEMPERATURE RANGE	-20~+45°C

MODEL NUMBER	POWER	LED CURRENT	COLOR TEMPERATURE	LUMINOUS FLUX (lm)	Beam angle (°)	COLOR RENDERING INDEX_CRI
TLd-15W	15W	350mA	● 2,700K	1088 ± 5%	15°, 24°, 38°, 60°	80+
			● 3,000K	1240 ± 5%		
			○ 4,000K	1360 ± 5%		
			○ 5,000K	1360 ± 5%		
TLd-25W	25W	620mA	● 2,700K	1905 ± 5%	24°, 38°, 60°, 90°	80+
			● 3,000K	2008 ± 5%		
			○ 4,000K	2156 ± 5%		
			○ 5,000K	2156 ± 5%		
TLd-36W	36W	900mA	● 2,700K	2803 ± 5%	24°, 38°, 60°, 90°	80+
			● 3,000K	2889 ± 5%		
			○ 4,000K	3054 ± 5%		
			○ 5,000K	3054 ± 5%		

3types of anti-glare lens narrow, medium & wide High efficient heat-sink design

